



P C B LAYOUT

**Specification:**

Current Rating: 3A

Insulation Resistance (Min.): 1000M Ω

Voltage Rating: 250V AC/DC

Contact Resistance (Max.): 20m Ω

Operation Temperature: -25 °C to +85 °C

Contact Material: Brass

Contact Plating: Nickel Plated Bottom 50μ and Gold Plated 0.8μ

Insulation Material: PBT (Black) (UL94V-0)

PART NO	A	B	C
ICF3-06S	26.92	16.76	5.08
ICF3-08S	29.46	19.30	7.62
ICF3-10S	32.00	21.84	10.16
ICF3-12S	34.54	24.38	12.70
ICF3-14S	37.08	26.92	15.24
ICF3-16S	39.62	29.46	17.78
ICF3-18S	42.16	32.00	20.32
ICF3-20S	44.70	34.54	22.86
ICF3-24S	49.78	39.62	27.94
ICF3-26S	52.32	42.16	30.48
ICF3-30S	57.40	47.24	35.56
ICF3-34S	62.48	52.32	40.64
ICF3-40S	70.10	59.94	48.26
ICF3-40S	75.18	65.02	53.34
ICF3-50S	82.80	72.64	60.96
ICF3-60S	95.50	85.34	73.66
ICF3-64S	100.58	90.42	78.7400

**Interface** INTERFACE CONNECTRONICS PVT LTD

Address:#85, Unit#3, 1st Floor, V.V. Yoga Saurabha, S. C. Road, Yeshwanthpur, Bangalore- 560 022.

Product Specification	2.54mm FRC Male Header Fully Shrouded Polarized Straight, Black						
Part no.	ICF3-XXS	Version	A0	Proportion			
Customer Code	TBA	Customer Part No.	TBA	Unit	mm		
Tolerance	X. ±0.50, X. ± 0.38, XX ± 0.25, XXX ± 0.13			File No.	TBA		
Drawn By	SM	Checked by	RKS	Approved by	YRS	Date	12/3/2019