



P C B LAYOUT

Specification:

Current Rating: 3A

Insulation Resistance(Min): 1000MΩ

Voltage Rating: 250V AC/DC

Contact Resistance(Max.): 20mΩ

Operating Temperature: -25°C +85°C

Contact Material: Brass

Insulation: PBT+30% Glass Fiber UL94V-0

Plating: Nickle Plated 50μ, Gold Plated 0.8μ

PART NO	A	B	PART NO	A	B
ICB1-1S04	2.54	5.08	ICB1-1S42	50.80	53.34
ICB1-1S06	5.08	7.62	ICB1-1S44	53.34	55.88
ICB1-1S08	7.62	10.16	ICB1-1S46	55.88	58.42
ICB1-1S10	10.16	12.70	ICB1-1S48	58.42	60.96
ICB1-1S12	12.70	15.24	ICB1-1S50	60.96	63.50
ICB1-1S14	15.24	17.78	ICB1-1S52	63.50	66.04
ICB1-1S16	17.78	20.32	ICB1-1S54	66.04	68.58
ICB1-1S18	20.32	22.86	ICB1-1S56	68.58	71.12
ICB1-1S20	22.86	25.40	ICB1-1S58	71.12	73.66
ICB1-1S22	25.40	27.94	ICB1-1S60	73.66	76.20
ICB1-1S24	27.94	30.48	ICB1-1S62	76.20	78.74
ICB1-1S26	30.48	33.02	ICB1-1S64	78.74	81.28
ICB1-1S28	33.02	35.56	ICB1-1S66	81.28	83.82
ICB1-1S30	35.56	38.10	ICB1-1S68	83.82	86.36
ICB1-1S32	38.10	40.64	ICB1-1S70	86.36	88.90
ICB1-1S34	40.64	43.18	ICB1-1S72	88.90	91.44
ICB1-1S36	43.18	45.72	ICB1-1S74	91.44	93.98
ICB1-1S38	45.72	48.26	ICB1-1S76	93.98	96.52
ICB1-1S40	48.26	50.80	ICB1-1S78	96.52	99.06
			ICB1-1S80	99.06	101.6

Interface INTERFACE CONNECTRONICS PVT LTD

Address:#85, Unit#3, 1st Floor, V.V. Yoga Saurabha, S. C. Road,
Yeshwanthpur, Bangalore- 560 022.

Product Description	2.54mm Singal Row Berg Stick, Straight						
Part no.	ICB1-1SXX	Version	A0	Proportion			
Customer Code	TBA	Customer Part No.	TBA	Unit	mm		
Tolerance	X. ±0.50, X. ± 0.38, .XX ± 0.25, .XXX ± 0.13			File No.	TBA		
Drawn By	SM	Checked by	RKS	Approved by	YRS	Date	12/3/2019