



Description:

Insulation Resistance (MIN) : 100MOHMS.
 Rated Current: 1A AC/DC
 Rated Voltage: 250V AC/DC
 Withstanding Voltage (MIN) : 500VAC
 Contact Resistance (Max) : 20 mohms
 Contact Material: Phosphor Bronze
 Finish: Gold Plated over Nickel
 Insulation: PBT (Black) UL94v-0
 Operating Temperature: -40° c to +105° c

Part No:	A	B	Part No:	A	B
ICF13-06	8.00	2.54	ICF13-28	21.97	16.51
ICF13-08	9.27	3.81	ICF13-30	23.24	17.78
ICF13-10	10.54	5.08	ICF13-34	25.78	20.32
ICF13-12	11.81	6.35	ICF13-40	29.50	24.13
ICF13-14	13.08	7.62	ICF13-44	32.13	26.67
ICF13-16	14.35	8.89	ICF13-50	35.94	30.48
ICF13-18	15.62	10.16	ICF13-52	37.21	31.75
ICF13-20	16.89	11.43	ICF13-60	42.29	36.83
ICF13-24	19.43	13.97	ICF13-64	44.83	39.37
ICF13-26	20.70	15.24			

Interace INTERFACE CONNECTRONICS PVT LTD
 Address: #85, Unit#3, 1st Floor, V.V. Yoga Saurabha, S. C. Road, Yeshwanthpur, Bangalore- 560 022.

Product Specification	1.27mm Flact Cable IDC Socket					
Part no.	ICF13-XX	Version	A0	Proportion		
Customer Code	TBA	Customer Part No.	TBA	Unit	mm	
Tolerance	X. ±0.50, X. ± 0.38, XX ± 0.25, XXX ± 0.13			File No.	TBA	
Drawn By	NBC	Checked by	VN	Approved by	YRS	Date
						12/3/2019