



**Specification:**  
 Rated Current: 1.5A  
 Insulation Resistance (MIN): 1000MΩ  
 Rated Voltage: 250V AC/DC  
 Contact Impedance: 20mΩ MAX  
 Operating Temperature: -25° C to +85° C  
 Contact Material: Brass  
 Insulation Material: PBT (Black) IL94v-0  
 Plating: Nickel Plated

PART #	A	B	C
ICF8-06	5.00	11.20	4.00
ICF8-08	7.00	13.20	6.00
ICF8-10	9.00	15.20	8.00
ICF9-12	11.00	17.20	10.00
ICF8-14	13.00	19.20	12.00
ICF8-16	15.00	21.20	14.00
ICF8-18	17.00	23.20	16.00
ICF8-20	19.00	25.20	18.00
ICF8-24	23.00	29.20	22.00
ICF8-26	25.00	31.20	24.00
ICF8-30	29.00	35.20	28.00
ICF8-34	33.00	39.20	32.00
ICF8-40	39.00	45.20	38.00
ICF8-44	43.00	49.20	42.00
ICF8-50	49.00	55.20	48.00

**Interace** INTERFACE CONNECTRONICS PVT LTD

Address:#85, Unit#3, 1st Floor, V.V. Yoga Saurabha, S. C. Road, Yeshwanthpur, Bangalore- 560 022.

Product Specification	2.00mm IDC Socket with Strain Relief, Black					
Part no.	ICF8-XX	Version	A0	Proportion		
Customer Code	TBA	Customer Part No.	TBA	Unit	mm	
Tolerance	X. ±0.50, X. ± 0.38, .XX ± 0.25, .XXX ± 0.13			File No.	TBA	
Drawn By	SM	Checked by	RKS	Approved by	YRS	Date
						12/3/2019