



Specification:
 Rated Current: 2A
 Insulation Resistance: 1000MΩ
 Rated Voltage: 250V AC/DC
 Contact Impedance: 15mΩ MAX
 Operating Temperature: -40° C to +105° C
 Contact Material: Brass
 Insulation Material: PBT (Black) IL94v-0
 Plating: Nickel Plated

PART #	A	B	C
ICF9-06S	13.34	4.00	12.24
ICF9-08S	15.34	6.00	14.24
ICF9-10S	17.34	8.00	16.24
ICF9-12S	19.34	10.00	18.24
ICF9-14S	21.34	12.00	20.24
ICF9-16S	23.24	14.00	22.24
ICF9-20S	27.34	18.00	26.24
ICF9-24S	31.34	22.00	30.24
ICF9-26S	33.34	24.00	32.23
ICF9-30S	37.34	28.00	36.24
ICF9-34S	41.34	32.00	40.24
ICF9-40S	47.34	38.00	46.24

Interface INTERFACE CONNECTRONICS PVT LTD							
Address:#85, Unit#3, 1st Floor, V.V. Yoga Saurabha, S. C. Road, Yeshwanthpur, Bangalore- 560 022.							
Product Specification	2.00mm FRC Box Header Straight, Black						
Part no.	ICF9-XXS	Version	A0	Proportion			
Customer Code	NA	Customer Part No.	NA	Unit	mm		
Tolerance	X. ±0.50, X. ± 0.38, .XX ± 0.25, .XXX ± 0.13			File No.	NA		
Drawn By	SM	Checked by	RKS	Approved by	YRS	Date	12/3/2019