



Description:

1. Material:

- a. Housing: PA9T Glass Fibre UL94 V-0; Black/White
- b. Contact: Brass T=0.25±0.02mm (Surface Plating: Au30~+Sn80~100~+Ni150u~80u~)
- c. Shell: SPCC T=0.30±0.02mm (Surface Plating: Cu80u~100u~+Ni80u~100u~)

2. Electric:

- a. Contact Resistance: 30 MilliΩ Max
- b. Insulation Resistance: 1000 MegaΩ Min
- c. Dielectric Voltage: 500V AC one sec level
- d. Operating Temperature: 0° C~50° C
- e. Power plug, insert with the greatest 3.5KG, pull out the power of the minimum 1.0KG

Interace INTERFACE CONNECTRONICS PVT LTD							
Address:#85, Unit#3, 1st Floor, V.V. Yoga Saurabha, S. C. Road, Yeshwanthpur, Bangalore- 560 022.							
Product Description	USB 2.0 A Male SMT Straight						
Part no.	ICU1-MK	Version	A0	Proportion			
Customer Code	TBA	Customer Part No.	TBA	Unit	mm		
Tolerance	X. ±0.50, X. ± 0.38, .XX ± 0.25, .XXX ± 0.13			File No.	TBA		
Drawn By	NBC	Checked by	VN	Approved by	YRS	Date	02/08/2024