


PIN CONFIGURATION		
SIDE A	COLOUR	SIDE B
PIN#1	RED	PIN#1
PIN#2	WHITE	PIN#2
PIN#3	GREEN	PIN#3
PIN#4	BLACK	PIN#4
SHELL	BRAID	SHELL

FINISHED GOOD(CA) PART NO: DESCRIPTION



RCA-9101: USB 2.0 A MALE TO A MALE CABLE ASSEMBLY WITH 26AWG/1P+24AWG/2C CABLE

RCA-9100: USB 2.0 A MALE TO A MALE CABLE ASSEMBLY WITH 28AWG/1P+24AWG/2C CABLE



RCA-9099: USB 2.0 A MALE TO A MALE CABLE ASSEMBLY WITH 28AWG/1P+28AWG/2C CABLE

LENGTH OF CA
0.1 TO XX MTRS

FOR EXAMPLE;

PART NO: RCA-9100-2-01
DISC: USB 2.0 A MALE TO A MALE CABLE WITH 28AWG/1PR+24AWG/2C USB CABLE LENGTH: 2MTR


CABLE CONSTRUCTION



SIDE A

USB SHIELDED HIGH SPEED CABLE 2.0 REVISION XX AWG/1P + XX AWG/2C E486063 AWM 2725 80°C 30V INTERFACE

XXX±20



SIDE B



SL NO	DESCRIPTION	QTY
1	USB SHIELDED HIGH SPEED CABLE 2.0 REVISION XX AWG/1P + XX AWG/2C E486063 AWM 2725 80°C 30V INTERFACE	1NOS
2	USB A MALE, SOLDER TYPE CONNECTOR	2NOS

		Description	USB 2.0 A MALE TO A MALE CABLE			
		Drg No	A4-01-9XXX-XXX-01			
		ICPL Part NO:	RCA-9XXX-XX-01			
Address: B-260,Peenya 2nd stage,Peenya industrial area, Bangalore-560058.		Customer Part No	TBA	Rev	00	
Drafted by	MC	Angle of projections	Third angle	Scale	1:1	
Checked	RV	Date:	18-12-2023	Sheet	1 of 1	
Approved	NC	All dimensions are in mm			Size:	A4
Tolerance :		<small>Unless otherwise specified for length</small> 0 - 500 - ±5 1000 - 1500 - ±15 500 - 1000 - ±10 1500 - 2000 - ±20				