



Product: [BAGU12QA006BK](#)

Outdoor OFC CLT (jelly filled) : GLASS YARNS+CST+Single PE Jacket with Steel Wire Embedded, 6F, G652.D, Anti-rodent & UV

Product Description

Outdoor optical fiber Central Loose Tube (jelly filled) cable with glass yarns as flexible non-metallic strength member, Corrugated steel tape armor and Single Polyethylene Jacket (black) with two steel wires embedded, 6 Fibers, G652.D, Anti-rodent & UV resistance

Technical Specifications

Product Overview

Suitable Applications:	For outdoor use in structured (data) wiring systems such as industrial backbone, campus backbone cabling. For outdoor use in networks for industrial, telecom, cable TV and/or broadcast. Easy to install in ducts, tunnels and trenches and/or tubes. Suitable for Direct Burial.
------------------------	--

Fiber Specifications

Fiber Type:	OS2, G.652.D
Fiber Core Diameter:	125 µm
Fiber Buffer Material:	PBT – Polybutylene Terephthalate
Fiber Count:	6
Fiber Color Coding:	TIA-598-D

Cable Construction

Subunit Waterblocking:	Gel Filled
------------------------	------------

Inner Jacket Specifications

Inner Jacket Strength Member:	Glass Yarns
Number of Inner Jacket Ripcords:	2

Armor Specifications

Armor Type and Material:	CST - Corrugated Steel Tape
--------------------------	-----------------------------

Outer Jacket Specifications

Jacket Material:	PE - Polyethylene
Nom. Diameter:	9.2 mm (0.36 in)
Outer Jacket Color:	Black

Optical Characteristics

Wavelength	1310 nm	1550 nm
Max. Attenuation	0.36 dB/km	0.22 dB/km
Mode Field Diameter	9.2 µm	10.4 µm

Mechanical Characteristics

Minimum Bend Radius During Installation:	20 x OD
Max. Tensile Strength During Installation:	2000 N, Passes IEC 60794-1
Max. Tensile Strength During Operation:	600 N, Passes IEC 60794-1
Crush Resistance:	3000 N/100mm, Passes IEC 60794-1

Bulk Cable Weight:	85 kg/km (57 lbs/1000ft)
--------------------	--------------------------

Temperature Range

Operating Temperature Range:	- 40°C To + 70°C
------------------------------	------------------

Standards and Compliance

Environmental Suitability:	OutdoorAerialDirect Burial, Outdoor, Sunlight Resistance, UV Resistance, Burial
ISO/IEC Compliance:	IEC 60793-1-1IEC 60794-1-1
European Directive Compliance:	EU Directive 2011/65/EU (RoHS 2)

History

Update and Revision:	Revision Number: 0.22 Revision Date: 02-13-2025
----------------------	---

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.