

## Interface<sup>®</sup> Basic Smart PDU Single Phase 250V 16A, Inlet C20, Outlet 8 x Combo C13/ C15/ C19/ C21, 1U Rack Mount

SKU - IC-SMARTPDU-01



Enhance your data centre's efficiency with the Basic Smart PDU, designed for optimal power distribution. This single-phase PDU operates at 250V and 16A, featuring a C20 inlet and eight versatile outlets (C13, C15, C19, C21) to accommodate various devices. Its 1U rack mount design ensures a sleek and organized setup, making it an essential component for any professional environment. Invest in reliable power management and streamline your operations with this essential tool.

### Specifications

INPUT	
Input Type(Rear)	IEC C20
Input Voltage	200-250V AC
Input Current	16A
Input Frequency	50/ 60 Hz
OUTPUT	
Display	LCD Touch
Output Type	IEC C13/ C15/ C19/ C21
Output Quantity	8 x Combo Outlet
Max.Output/ Socket	16A
Meter/ Switch	Available per outlet
Monitoring	Current value warning to be set manually
Outlet Scheduling	Available
Remote Monitoring	Software to remotely monitor PDU

<b>PHYSICAL</b>	
Max.Height	44.2
Max.Width	481.00
Max.Depth	200.00
Net Weight(kg)	2.7
Gross Weight(kg)	2.8
Colour	Black
Storage Temperature	-15°C ~ 55°C
<b>NETWORK CONNECTIVITY</b>	
IP	Dynamic/ Static
Daisy Chain	Supports upto 5 units
Network Port	1 * RJ45 with LED Indicator, 10/100/1000 Mbps
USB Port	2*USB 2.0 for Daisy Chain,1*USB 2.0 for Firm Upgrade
<b>CONFORMANCE</b>	
Product Compliance	RoHS and REACH compliant
Safety Approvals	IEC 61000-6-3, IEC61000-6-1, EN55035, EN55032, IEC62368-1
<b>WARRANTY</b>	
Product Warranty	One year limited warranty

Interface Connectronics Pvt Ltd  
#85, Unit 3, First Floor, Yeshwanthpur,  
Bangalore -560 022  
India

E: [sales@icpl.co.in](mailto:sales@icpl.co.in)  
T: +91 97399 52969  
[www.icplindia.com](http://www.icplindia.com)