

Interface® Basic Smart PDU Single Phase PDU 125V 20A, Inlet C20, Outlet 8 x Combo C13/ C15/ C19/ C21, 1U Rack Mount

SKU - IC-SMARTPDU-03



Enhance your data centre's efficiency with the Basic Smart PDU, designed for optimal power distribution. This single-phase PDU operates at 125V and 20A, featuring a C20 inlet and eight versatile outlets (C13, C15, C19, C21) to accommodate various devices. Its 1U rack mount design ensures a sleek, space-saving solution for your server racks, making it an essential addition for any IT infrastructure. Invest in reliable power management and streamline your operations with this robust PDU.

Specifications

INPUT	
Input Type(Rear)	IEC C20
Input Voltage	200-250V AC
Input Current	20A
Input Frequency	50/ 60 Hz
OUTPUT	
Display	LCD Touch
Output Type	IEC C13/ C15/ C19/ C21
Output Quantity	8 x Combo Outlet
Max.Output/ Socket	20A
Meter/ Switch	Available per outlet
Monitoring	Current value warning to be set manually
Outlet Scheduling	Available
Remote Monitoring	Software to remotely monitor PDU

PHYSICAL	
Max.Height	44.2
Max.Width	481.00
Max.Depth	200.00
Net Weight(kg)	2.8
Gross Weight(kg)	2.9
Colour	Black
Storage Temperature	-15°C ~ 55°C
NETWORK CONNECTIVITY	
IP	Dynamic/ Static
Daisy Chain	Supports upto 5 units
Network Port	1 * RJ45 with LED Indicator, 10/100/1000 Mbps
USB Port	2*USB 2.0 for Daisy Chain,1*USB 2.0 for Firm Upgrade
CONFORMANCE	
Product Compliance	RoHS and REACH compliant
Safety Approvals	IEC 61000-6-3, IEC61000-6-1, EN55035, EN55032, IEC62368-1
WARRANTY	
Product Warranty	One year limited warranty

Interface Connectronics Pvt Ltd
#85, Unit 3, First Floor, Yeshwanthpur,
Bangalore -560 022
India

All logos and trademark are property of their respective owners.

*Includes poly-bag

E: sales@icpl.co.in
T: +91 97399 52969
www.icplindia.com