

Interface[®] Basic Smart PDU Single Phase PDU 250V 16A, Inlet C20, Outlet 6 x C13 + 2 x C19, 1U Rack Mount

SKU - IC-SMARTPDU-04



Enhance your data centre's efficiency with the Basic Smart PDU, designed for optimal power distribution. This single-phase PDU operates at 250V and 16A, featuring a C20 inlet and a versatile outlet configuration of 6 x C13 and 2 x C19, making it ideal for various equipment setups. Its 1U rack mount design ensures a space-saving solution while providing reliable power management, perfect for any server rack environment. Upgrade your power infrastructure today and experience seamless performance and reliability.

Specifications

INPUT	
Input Type(Rear)	IEC C20
Input Voltage	200-250V AC
Input Current	20A
Input Frequency	50/ 60 Hz
OUTPUT	
Display	LCD Touch
Output Type	IEC C13 and C19
Output Quantity	6 x C13 + 2 x C19
Max.Output/ Socket	20A
Meter/ Switch	Available per outlet
Monitoring	Current value warning to be set manually
Outlet Scheduling	Available
Remote Monitoring	Software to remotely monitor PDU

PHYSICAL	
Max.Height	44.2
Max.Width	481.00
Max.Depth	201.00
Net Weight(kg)	2.9
Gross Weight(kg)	3
Colour	Black
Storage Temperature	-15°C ~ 55°C
NETWORK CONNECTIVITY	
IP	Dynamic/ Static
Daisy Chain	Supports upto 5 units
Network Port	1*RJ45 with LED Indicator, 10/100/1000 Mbps
USB Port	2*USB 2.0 for Daisy Chain,1*USB 2.0 for Firm Upgrade
CONFORMANCE	
Product Compliance	RoHS and REACH compliant
Safety Approvals	IEC 61000-6-3, IEC61000-6-1, EN55035, EN55032, IEC62368-1
WARRANTY	
Product Warranty	One year limited warranty