

Interface® High Density Smart PDU Single Phase 240V 63A, Inlet IEC60309, Outlet 36 x Combo C13/ C15/ C19/ C21, 0U Rack Mount

SKU - IC-SMARTPDU-07

Experience unparalleled power management with our High Density Smart PDU, designed for single-phase applications at 240V and 64A. Featuring an IEC60309 inlet and an impressive array of 36 combo outlets (C13, C15, C19, C21), this 0U rack mount solution maximizes your space while providing versatile connectivity for all your devices. Ideal for data centers and server rooms, it ensures efficient power distribution and enhances your operational efficiency, making it a must-have for any professional setup. Upgrade your power infrastructure today and enjoy reliable performance and flexibility.

Specifications

| INPUT | |
|--------------------------|---|
| Input Type(Rear) | IEC60309, 4.0mm ² *5C, NEMA L6-30P 2P+E 6h |
| Input Voltage | 240V AC |
| Input Current | 63 A |
| Input Frequency | 50/ 60 Hz |
| Circuit Breaker | 3 x 20 A (MCB) |
| OUTPUT | |
| Display | LCD |
| Output Voltage | 208~240VAC |
| Output Quantity | 36 x IEC3020 Combo C13/ C15/ C19/ C21 |
| Meter/ Switch | Available per outlet |
| Monitoring | Current value warning to be set manually |
| Outlet Scheduling | Available |
| Remote Monitoring | Software to remotely monitor PDU |
| Measurement | Ampere, Frequency (Hz), kVA, kW, kWh, Power Factor, Volts |
| Accuracy | ±1% |
| PHYSICAL CHARACTERISTICS | |
| Max. Height (mm) | 77.00 |
| Max. Length (mm) | 1860.00 |
| Max. Depth (mm) | 76.00 |
| Weight (kg) | 10.4 |
| Colour | Black |
| Material | Metal |



| TEMPERATURE RATING | |
|----------------------------|---|
| Operating Temperature | 0 ~ 60°C |
| Storage Temperature | -15°C ~ 55°C |
| NETWORK CONNECTIVITY | |
| IP | Dynamic/ Static |
| Daisy Chain | 2*RS485 Ports Supports up-to 5 units |
| Giga Ethernet Network Port | 1*RJ45 with LED Indicator, 10/100 Mbps |
| USB Port | 1*USB 2.0 for Firmware Upgrade |
| TH Port | 1 Temperature/ Humidity Sensor Port |
| Ethernet Communication | HTTP; SNMP v1/v2c/v3; DHCP |
| Hot-Swap Controller | Replace/ service module while PDU is powered on |
| CONFORMANCE | |
| Product Compliance | RoHS and REACH compliant |
| WARRANTY | |
| Product Warranty | One year limited warranty |



Interface Connectronics Pvt Ltd
#85, Unit 3, First Floor, Yeshwanthpur,
Bangalore -560 022
India

All logos and trademark are property of their respective owners.
*Actual device may differ from the image shown.

E: sales@icpl.co.in
T: +91 97399 52969
www.icplindia.com