



PIN CONFIGURATION (STRAIGHT)		
SIDE A	COLOUR	SIDE B
PIN#1	BLACK	PIN#1
PIN#2	BROWN	PIN#2
PIN#3	RED	PIN#3
PIN#4	ORANGE	PIN#4
PIN#5	YELLOW	PIN#5
PIN#6	GREEN	PIN#6
PIN#7	BLUE	PIN#7
PIN#8	GREY	PIN#8
PIN#9	WHITE	PIN#9
DRAIN	SHELL	DRAIN

PIN CONFIGURATION (CROSS)		
SIDE A	COLOUR	SIDE B
PIN#1	BLACK	PIN#9
PIN#2	BROWN	PIN#8
PIN#3	RED	PIN#7
PIN#4	ORANGE	PIN#6
PIN#5	YELLOW	PIN#5
PIN#6	GREEN	PIN#4
PIN#7	BLUE	PIN#3
PIN#8	GREY	PIN#2
PIN#9	WHITE	PIN#1
DRAIN	SHELL	DRAIN

FINISHED GOOD(CA) PART NO: DESCRIPTION

RCA-301X XX 01

TYPE OF CA LENGTH OF CA COLOUR OF CA

0.1 TO XX MTRS BLACK

RCA-3015: D SUB MALE TO MALE CABLE ASSEMBLY WITH 9 CORE 28AWG +AE ROHS COMPLIANT-STRAIGHT

RCA-3016: D SUB MALE TO MALE CABLE ASSEMBLY WITH 9CORE 28AWG +AE ROHS COMPLIANT-CROSS

FOR EXAMPLE;
PART NO: RCA-3015-1-01
DESC: D SUB MALE TO MALE WITH 9 CORE CABLE STRAIGHT CONNECTION
LENGTH: 1MTR

SL NO	DESCRIPTION	QTY
1	INTERFACE UL AWM 2725 9 CORE 28AWG+AE ROHS COMPLIANT	1NOS
2	D-SUB-SOLDER-CONNECTOR-MALE-09PIN	2NOS
3	THUMB SCREW	4NOS
4	HEAT SHRINK SLEEVE 1MM	2NOS

		Description		D SUB 9 PIN MALE TO MALE WITH 9 CORE SHIELDED CABLE STRAIGHT AND CROSS CONNECTION	
		Drg No		A4-01-301X-XXX-01	
		ICPL Part No		RCA-301X-XX-01	
Address: B-260,Peenya 2nd stage,Peenya industrial area, Bangalore-560058.		Customer Part No	TBA	Rev	00
Drafted by	MC	Angle of projections	Third angle	Scale	1:1
Checked	RV	Date	25-06-2024	Sheet	1 of 1
Approved	NC	All dimensions are in mm		Size	A4
Tolerance	Unless otherwise specified for length 0 - 500 - ±5 1000 - 1500 - ±15 500 - 1000 - ±10 1500 - 2000 - ±20	*The document is a property of Interace Connectronics Pvt Ltd and is considered company confidential. Reproduction, unauthorised use, or disclosure of this drawing in whole or in part is prohibited.*			